



**Table E  
Cable Seals**

89085	.23 - .29 in. (6-7.5 mm)	10/Pk
89086	.29 - .35 in. (7.5-9 mm)	10/Pk
89087	.35 - .41 in. (9-10.5 mm)	10/Pk
89088	.41 - .47 in. (10.5-12 mm)	10/Pk
89093	.47 - .55 in. (12-14 mm)	10/Pk
89094	.55 - .63 in. (14-16 mm)	10/Pk
89095	.63 - .71 in. (16-18 mm)	10/Pk
89096	.71 - .79 in. (18-20 mm)	10/Pk
89103	.79 - .87 in. (20-22 mm)	10/Pk
89104	.87 - .95 in. (22-24 mm)	10/Pk
89105	.94 - 1.02 in. (24-26 mm)	10/Pk
89106	1.02 - 1.10 in. (26-28 mm)	10/Pk



**Table F  
Cable Seal Plugs**

89125	.23 - .29 in. (6-7.5 mm)	
89126	.29 - .35 in. (7.5-9 mm)	
89127	.35 - .41 in. (9-10.5 mm)	
89128	.41 - .47 in. (10.5-12 mm)	
89129	.47 - .55 in. (12-14 mm)	
89130	.55 - .63 in. (14-16 mm)	
89131	.63 - .71 in. (16-18 mm)	
89132	.71 - .79 in. (18-20 mm)	
89133	.79 - .87 in. (20-22 mm)	
89134	.87 - .94 in. (22-24 mm)	
89135	.94 - 1.02 in. (24-26 mm)	
89136	1.02 - 1.10 in. (26-28 mm)	



## MetaFlux Chain Lubricant

A fully synthetic, special chain grease for use in lubrication of the Tornado's drive chain. Can also be used as a superior lubricant on any other machine which uses a chain.

- ▶ Temperature ranged from 5° F to 480° F (-15° C to 250° C)
- ▶ High penetration, powerful adhesion, no drips
- ▶ Stable viscosity, and no effect on regular O-rings
- ▶ Non-soiling, colorless, free of silicone and solid matter
- ▶ Transparent with corrosion resistance up to one year
- ▶ Long term protection even with high dust occurrence, resistant to hot and cold water

P/N 89153 Weight: 13.5 oz. (400 ml)



## Air Glide Duct Lube

A silicone-based synthetic lubricant specifically designed to pre-lubricate the interior of ducts prior to cable blowing.

- ▶ Compatible with all cable jacket and innerduct materials
- ▶ 1 quart when blown into a 1.25 in. (32 mm) ID duct with a sponge will effectively coat 1000 ft. (305 M)
- ▶ Non-flammable
- ▶ Low odor
- ▶ Not water soluble
- ▶ Usable at all temperatures

P/N 89138 Weight: 25 lbs (11.5 kg.) per case. Sold in case of 12 quarts

