

Accelair 2 Configuration for Cable Blowing




Polymeric Fiber Buckle Plates includes 5 Buckle Shuttles

P/N	Description
89487	1.4mm



Stainless Fiber Buckle Plates includes 5 Buckle Shuttles


P/N	Description
89440	1.0mm
89441	1.2mm
89442	1.4mm
89443	1.5mm



Stainless steel buckle plates are recommended to withstand abrasive coatings when using EPFU fibers

Fiber Blowing Plates Polymeric

P/N	Description	P/N	Description
89461	1.4mm	89471	2.4mm
89462	1.5mm	89472	2.5mm
89463	1.6mm	89473	2.6mm
89464	1.7mm	89474	2.7mm
89465	1.8mm	89475	2.8mm
89466	1.9mm	89476	2.9mm
89469	2.2mm	89477	3.0mm



Fiber Blowing Plates



Spare Lower Plate Seals
5/pk

Spare Lower Plate Seals 5/pk

P/N	Description
89437	Seal 5/pk

Stainless Blowing Plates

P/N	Description
89657	1.6mm
89658	1.7mm
89661	2.0mm
89662	2.1mm
89674	2.3mm
89666	2.5mm
89671	3.0mm



Spare Buckle Shuttles
5/pk

Spare Buckle Shuttle 5/pk

P/N	Description
89436	Shuttles 5/pk

Tube Clamps and Seals includes 5 Tube Seals

P/N	Description
89491	3mm
89492	4mm
89493	5mm
89494	6mm
89495	7mm
89496	8mm
89497	8.5mm
89498	10mm



Tube Clamp and Seals

Spare Tube Seals 5/pk

P/N	Description
89936	3mm
89937	4mm
89938	5mm
89939	6mm
89940	7mm
89941	8mm
89942	8.5mm
89953	10mm

Infeed Guides

P/N	Description
89478	.8 - 2.0mm
89479	2.0 - 3.0mm



Infeed Guides

Spare Tires 10/pk

P/N	Description
89503	Up to 2.0mm
89508	2.0 - 3.0mm



Accelair 2 Accessories

Description	Order Code
5mm Clear Tube Connector (Pack of 5)	89710
Air Flow Meter	89703

Other sizes of clear tube connector are available. Air flow meter can be used to check route integrity. Please contact the GMP sales office to order or enquire about parts not listed; always quoting the machine type and serial number.

Air Flow Meter



5mm Clear Tube Connector
(Pack of 5)

Accelair 2 Bottled Nitrogen Kit for Blown Fiber

Used with bottled nitrogen in place of a compressor for 5mm or smaller Microduct

- Quickly connects to the Accelair 2 via a quick coupling.
- Hose is 10 feet long for easy setups.
- The regulator has easy to read 2" gauges.
- The flexible hose is abrasion, weather and ozone resistant.
- Inlet connection is CGA 580.



Do Not Exceed the Hose Rating of 200 PSI.

Accelair 2 Bottled Nitrogen Kit
P/N 74080 Weight: 5 lbs. (2.3 kgs)



GMP • 3111 Old Lincoln Hwy • Trevose, PA 19053 • USA
TEL: +1-215-357-5500 • www.gmptools.com