Gentle Air Blown Fiber Blowing Machine

Now you can depend on the same GMP quality as our larger machines in a new smaller package... The Gentle Air uses compressed air to install the fiber. Coupled with the driven roller is a precision clutch that you can dial in your custom torque from zero to infinity. The rollers, powered by most types of cordless drills (not included), control the blown fiber as it is propelled into the microduct. An electronic monitoring system provides read-outs of speed and distance.

The design of the Gentle Air provides for quick and easy component changes for different cable or duct sizes. Its compact size and portable maneuverability make the Gentle Air ideally suited for external or inbuilding use.

Main Features:

- Installs cable diameters of 0.039" to 0.118" (1.0 to 3.0mm)
- Digital cable speed and length monitoring
- Accommodates microduct sizes of 4 to 8.5mm (OD)
- Integral air valve and pressure gauge
- Uses a fully adjustable precision clutch for torque control
- Low maintenance
- Uses most variable speed drills as a power source
- Lightweight, durable construction with precision machined parts
- Travel bag included

•	IIa	ver bag included		
•	Sin	gle person operation		PV)
				\sim
	P/N	COMPONENT		
	TUBE	COLLET AND CLAMP ASSEMBLIES		
	CHOOSE	ONE SIZE BELOW FOR STANDARD GENTLE AIR	1	
	89918	4mm	1	
	89919	5mm	1	
	89926	7mm	1	
	89927	8mm	1	
	89920	8.5mm	1	
	CABLE	KIT SEAL COLLET ASSY		
CABLE KIT SEAL COLLET ASST CHOOSE ONE SIZE DUCT SEAL BELOW FOR STANDARD GENTLE				
	89898	2.0-2.5mm	1	
	89899	2.5-3.0mm	1	
	89929	1.0-2.0mm	1	

How To Chose Your Gentle Air Component Kits


When choosing the Base Model: (items priced individually)

- Pick 1 Tube and collet and clamp assembly
- Pick 1 Cable seal collet assembly

When choosing the Plus Model: (included in price) Receive all components to blow the 3 most popular sizes

Supplied With All Machines

Gentle Air Cable Blowing Machine (2) 9V Lithium Batteries Toolkit Travel bag Manual





Specifi cations:

Cable Diameter: 0.039" to 0.118" (1.0 to 3.0mm) Tube Size (Outside Dia): (OD) 0.158" to 0.275" (4 to 8.5mm) Cable Speed (Adjustable): 0-300 ft/min (0-90m/min) Max Air Pressure: 220 psi (15 Bar) Power Requirement: Variable Speed Drill Width: 8.1 in. (206mm) Length: 9.7 in. (246mm) Height: 8.5 in. (216mm) Weight: Approx. (5.4Kgs Approx.)

Up to 30% savings on accessories when purchasing the Plus



Tube Collet and Clamp Assemblies



Cable Seal Collet Assemblies